



FEATURES

- ▼ Suitable for use with 40w incandescent lamps.
- ▼ Flush mount step light with low profile.
- ▼ Housing and louver frame available in corrosion resistant rugged cast marine brass or copper free aluminum.
- ▼ 814 and 824 models include cover with flush or surface mount louver over a tempered glass lens to reduce glare and direct light to stairs or surface hazard. 816 model includes tempered glass lens only.
- ▼ Choice of corrosion resistant cover with an oven-cured polyester powder coated finishes in dark bronze or light gray.
- ▼ 5 year warranty.


APPROVALS

- ▼ UL 1598A - Marine Outside Type Saltwater
- ▼ ABS
- ▼ Conforms to IP 66

APPLICATIONS

- ▼ Marine and wet environments
- ▼ Offshore oil and gas platforms
- ▼ Drill ships and exploration vessels
- ▼ Tankers
- ▼ Gangway/walkway steps
- ▼ Surface level height marking

DIMENSIONS



Dimensions in inches



MARINE, OUTSIDE AND CORROSIVE ENVIRONMENTS WATERTIGHT STEP LIGHTS

LUMINAIRE TECHNICAL SPECIFICATIONS

HOUSING AND LENS FRAME

Available in cast marine brass or copper free aluminum.

COVERS

Choice of oven-cured polyester powder coated cast marine brass with a dark bronze protective finish or copper free aluminum with an light gray protective finish.

OUTLETS

All units are supplied undrilled as standard. Optional outlets are available on all sides of the luminaire up to a maximum of 1" NPT.

LAMPHOLDER

A porcelain medium base lampholder is supplied as standard.

HARDWARE

Stainless steel.

VOLTAGE OPERATION

All luminaires are supplied rated to operate on 250v AC 60Hz.

LAMP TYPE

The luminaire is suitable for lamps up to 40w A-19 maximum. All luminaires are supplied without lamps.

LENS

A clear impact resistant glass lens is provided as standard on louver units. A frosted lens is supplied on plain step light units.

GASKETS

One piece silicone gasket provides a watertight seal between the lens frame and housing.

ORDERING REFERENCES

INCANDESCENT LUMINAIRES				
DESCRIPTION	LAMP SIZE	ALUMINUM WEIGHT (lbs)	MARINE BRASS TYPE (B)	ALUMINUM TYPE (A)
Step Light with Surface Louver	40w A-19	9.5	814S	814AS
Step Light Plain Frosted	40w A-19	9.5	816S	816AS
Step Light with Flush Louver	40w A-19	12.0	824S	824AS

SPARE PARTS			
LAMP HOLDERS		LAMPS	
Porcelain	INX4088	40w A-19	INX3531
GLASS LENS		GASKETS	
Surface Louver	INX2114	Lens Frame	GKT5024
Plain Frosted	INX2002	Mounting	GKT5089
Flush Louver	INX2111		